

BEST

BREATHE-EZ PAINT

5205 Ballard Ave. N.W.
Seattle, WA 98199
<http://www.bestpaintco.com>

Material Safety Data Sheet For Coatings and Related Materials

Prep: Jan. 1994 Update: June 2005

Sections I-IV (This Page) / Sections V-X ([Click Here](#))

Section I – Product Identification

Product Number: BEZ082
Product Name: Breathe-EZ Clear Coat for Wood
Product Class: Vinyl Acrylic Latex

24 Hour Emergency Assistance

Information (Best Paint) (206) 783-9938

<i>Hazard Rating</i>	<i>This Product</i>
0 Lowest	Health: 0
1	Flammability: 0
2	Reactivity: 0
3	Personal Protection: E
4 Extreme	

Hazardous Material: Yes: No: XX
EPA Registration Number (if applicable): N/A

Section II – Hazardous Ingredients

<i>Ingredient</i>	<i>CAS Number</i>	<i>Percent (By Weight)</i>	<i>Occupational Exposure TLV (ACGIH) PEL (OSHA)</i>
N/A			

“No reportable quantities of hazardous ingredients are present. Not toxic chemical(s) subject to the reporting requirements of section 313 of title III and of 40 CFR 372 are present. The materials in this product have not been listed by NTP, IARC and OSHA as Carcinogenic.”

Section III – Physical Data

Boiling Point: 212 F. (Water)	Weight/Gallon: 11.9 lbs	Vapor Pressure: mmHg @20degC N/A
Vapor Density:	Heavier than Air: XX	Lighter Air:
Evaporation Rate: (Butyl Acetate=1)	Faster than Ether:	Slower than Ether: XX
Percent Organic Volatile by Volume: 0		Solubility in Water: Infinite
VOC: 0 Grams/Liter (Less Water)		Reactivity in Water: None
Melting Point: Unknown	pH: 7-8	Viscosity: 95+KU
Freezing Point: 32 F.		

Appearance & Odor: Thixotropic Liquid with slight to no odor, color of tint.

Section IV – Fire and Explosion Hazard Data

Flammability Classification:	OSHA: Nonflammable	Flash Point: N/A TCC
DOT Proper Shipping Name: Paint	Hazard Class: Not Restricted	LEL: N/A UEL: N/A
	DOT: Nonflammable	UN Number: N/A

Extinguishing Media: Foam, Dry Chemical, Water or Water Fog

Special Firefighting Procedures: Water may be used to cool and protect adjacent containers.

Unusual Fire & Explosion Hazards: Will not burn; closed containers may rupture when exposed to extreme heat or fire.

BEST

BREATHE-EZ PAINT

Section V: Health Hazard Data

PRIMARY ROUTE(S) OF EXPOSURE: Inhalation, Skin or Eye Contact, Ingestion.

EFFECTS OF ACUTE OVEREXPOSURE:

INHALATION: Prolonged inhalation, in confined areas, may lead to mucous membrane irritation, dizziness and headache.

SKIN CONTACT: Irritation of the skin.

EYE CONTACT: Irritation of the Eyes

INGESTION: Amounts ingested incidental to consumer and industrial handling are not likely to cause injury. However, ingestion of larger amounts could cause serious injury.

EMERGENCY AND FIRST AID PROCEDURES:

INHALATION: Remove to fresh air. If respiratory symptoms develop, seek medical attention at once.

SKIN CONTACT: Wash off quickly with plenty of water, then soap and water. Remove and wash contaminated clothing before reuse.

EYE CONTACT: Flush immediately with large amounts of water, especially under lids, for at least 15 minutes. Obtain emergency medical treatment.

INGESTION: If swallowed, obtain medical treatment immediately.

MEDICAL CONDITIONS AGGRAVATED BY CHRONIC OVEREXPOSURE: None, when used in accordance with safe handling instructions. (*See section VIII*)

CARCINOGENICITY: This product contains no known carcinogens in reportable quantities as defined by NTP, IARC, OSHA and EPA.

Section VI: Reactivity Data

STABILITY: Unstable: Stable: XX

HAZARDOUS POLYMERIZATION: May occur: Will Not occur: XX

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon Monoxide and Carbon Dioxide

CONDITIONS TO AVOID: Elevated temperatures, contact with oxidizing agents.

INCOMPATIBILITY: Oxidizers and/or Hydrofluoric Acid

Section VII: Spill or Leak Procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Comply with all applicable health and environmental regulations. Ventilate area. Spills may be collected with absorbent materials.

WASTE DISPOSAL: Dispose of according to local, state and federal regulations. Avoid discharge to natural waters.

Section VIII: Safe Handling and Use Information

Use only with adequate ventilation. Avoid breathing vapor and spray mist. Avoid contact with skin and eyes.

VENTILATION: Local exhaust preferable. General exhaust acceptable if the exposure to materials in section II is maintained below applicable exposure limits.

RESPIRATORY PROTECTION: If personal exposure cannot be controlled below applicable limits by ventilation, wear a properly fitter organic vapor/particulate respirator approved by NIOSH/OSHA for protection against materials in section II.

PROTECTIVE GLOVES: Wear gloves which are recommended by glove supplier for protection against materials in section II.

EYE PROTECTION: Wear safety spectacles with un-perforated side shields.

PERSONAL PROTECTIVE EQUIPMENT: Eye wash – Safety showers – Goggles – Safety glasses – Impervious gloves.

HYGIENIC PRACTICE: Keep work area clean and free from spills and leaks. Always wash hands thoroughly with soap and water before handling food, drink or smoking.

BEST *BREATH-EZ PAINT*

Section IX: Special Precautions: Keep out of the reach of children

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING: Avoid temperatures below 40° F. Keep from freezing. Store containers with lids tightly closed and appropriately labeled.

Section IX: Supplemental Information

NOTE: This product contains no mercury in reportable quantities as defined by OSHA and EPA. The information in this data sheet is believed to be accurate and true at the time of preparation of this document. This is not a warranty of product or product specification. The end-user of this product is advised to verify in advance that the information in this sheet is current, applicable and suitable to their circumstances.